



LEGEND	
BLACK	B
GREEN	G
BLUE	L
BROWN	N
ORANGE	O
PINK	P
RED	R
SILVER	S
VIOLET	V
WHITE	W
YELLOW	Y

WIRE IDENTIFICATION	
14 L CAB	(Blue line)
GAUGE COLOUR STAMP	(Arrow pointing to blue line)
18 WG	(Green line)
GAUGE COLOUR/TRACE COLOUR	(Arrow pointing to green line)

CUSTOMER	ISUZU								
HARNESS P/N	5901200412-03								
HARNESS NAME	TAIL END ADAPTOR SUIT NPS 200 / 300 AND NQR 200 / 300								
DATE	20-04-12								
BRAID COLOR	BLACK								
WIRE SPECS	<table border="1"> <tr> <td>BOOT SPEC</td> <td>XLPE 125 DEG WIRE</td> <td>BUSSED RECEPTACLES</td> <td>NO SOLDERED JOINTS</td> </tr> <tr> <td>TICK IF APPLICABLE</td> <td><input checked="" type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> </table>	BOOT SPEC	XLPE 125 DEG WIRE	BUSSED RECEPTACLES	NO SOLDERED JOINTS	TICK IF APPLICABLE	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
BOOT SPEC	XLPE 125 DEG WIRE	BUSSED RECEPTACLES	NO SOLDERED JOINTS						
TICK IF APPLICABLE	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>						

NOTE : WHERE A BOOT IS NOT USED THE LENGTH OF EXPOSED WIRE BETWEEN THE BACK EDGE OF THE CONNECTOR AND END OF BRAID / TUBING WILL BE 50mm FOR A 1 OR 2 WAY CONNECTOR + 2mm PER WAY / LOCATION FOR CONNECTORS OF MORE THAN 2 WAY.

NOTE : ALL MEASUREMENTS ARE TO THE BACK EDGE OF THE CONNECTOR HOUSING (WHERE THE WIRES GO IN)